

Bidbury & Co

MALVERN CARTRIDGE
REPLACEMENT INSTRUCTIONS



INSTALLATION INSTRUCTIONS

INSTALLATION INSTRUCTIONS




PLEASE READ THESE INSTRUCTIONS CAREFULLY AND KEEP IN A SAFE PLACE FOR FUTURE REFERENCE.

Please follow the instructions below for correct installation of your replacement tap cartridge.


ENSURE BOTH HOT AND COLD SUPPLIES ARE TURNED OFF BEFORE REMOVING ANY PARTS.

1



Using a number 3 allen key loosen (but DO NOT remove) the grub screw underneath the handle cover. Remove the handle and cover in one piece by pulling away from the tap body.

2




With the cover removed, gently prise the curved collar off from the inside, ensuring the tap surface is not damaged. Note its position for when you re-fit.

3



Using a 21 mm socket, remove the brass section that holds the cartridge in place. Be careful not to lose the O ring that sits inside of the brass section that you have just removed.

4




Remove the cartridge from the body of the tap

5



When replacing the new cartridge be sure to check the position using the two locating pins at the rear of the cartridge. see fig 6

6



Be careful when removing and replacing the cartridge that the O ring is in position and the locating pins are correctly oriented.

To install the new cartridge - reverse steps above. Turn water back on and check for any leaks.

For further assistance, please contact Bidbury & Co Customer Support at www.bidburyandco.com or 0333 33 55 956